

TYPHOON X40



Features

- Brushless DC Fan
- Independent fan and heater connections
- Compact
- Light weight

Options (contact us)

- Alternative Power
- Alternative Voltage
- Alternative Fan (12VDC)
- Mounting Bracket

DBK's knowledge of thermal management gives us the experience to guide and support you with your technical challenges - we can manage the complete project from concept to full production release.

Typhoon X40	100	200	300	350
Article Number	1130143	1130144	1130145	1130101
Nominal Power Output (10°C) [W]	100	200	300	350
Voltage Element (Voltage Fan) [V]	220-240 AC (24 DC Fan)			
Inrush current (230V) [A]	2	4	6.3	6.3
Connector	Screwless AWG 20 -14 (0.5 - 2.5mm ²)			
Dimensions (LxWxH) [mm]	76x52x93			
Mounting	Clip for DIN rail EN 60715 (optional bracket)			
Airflow Rate (fan nominal)	23 m ³ /hr (14 CFM)			
Fan Life Time – L10 (40°C) [hrs]	70,000			
Ingress Protection	IP20			
Operating Temperature Range [°C]	-40 to 70°C			
Protection Class	II			
Maximum Temperature	65°C except air exit grille			
Weight [g]	367			

Design Drawing

